



# ELEVATORS

[www.arskametalli.fi](http://www.arskametalli.fi)



# EFFICIENT AND RELIABLE GRAIN TRANSFER

Elevators made of galvanized steel convey the grain fast and reliably without damaging it.

Elevator structure is self-supporting. There are open belt pulleys in the head and bottom. Direct-drive gear motor is reliable in all conditions and almost maintenance-free. Design of the bottom allows maximum filling for the buckets – even with wet grain.



Elevator is easy to clean through large hatches. As an option, pre-cleaner A150 attached to top part keeps working area dust-free while conveying the grain.

Adjustable crop guide prevents grain to access back to elevator pipe. Replacement air comes through a gap on the intake pit inlet's upper edge. Structure enhances significantly grain's flow, and grain can be stored in the intake pit longer than usually.

ELEVATOR	A68	A92	A118
Capacity [t / h]	68	92	118
Motor power [kW]	4	5.5 / 7.5	7.5
Belt width [mm]	140	170	170
Bucket amount [pcs / m]	7	6	6
Bucket size [mm]	145	180	205
Elevator pipe [Ø mm]	210	280	280
3-way divider [Ø mm]	160	200	200





## STANDARD EQUIPMENTS

- ✓ Speed control
- ✓ 3-way divider
- ✓ Intake pit inlet
- ✓ Inlet 4 x Ø200

## OPTIONS


- + Pre-cleaner A150
- + Motored 3-way divider
- + Motored shutter
- + Inlet 2 x Ø200
- + Service platform
- + Supports



[www.arskametalli.fi](http://www.arskametalli.fi)

## ARSKAMETALLI OY

 Saarentaantie 33  
FI-31400 Somero, Finland

 +358 2 748 9700

 [posti@arskametalli.fi](mailto:posti@arskametalli.fi)

© Arskametalli Oy 2020

All rights reserved. In the photos in this brochure or other publications may occur devices which are not standard equipment. Technical specifications are approximate.