



# TANDEM DOUBLE DRYERS

[www.arskametalli.fi](http://www.arskametalli.fi)



# TWO DRYER MACHINERIES, ONE FRAME AND ONE HEAT SOURCE

Tandem double dryer has two dryers combined into one frame to create a dual batch dryer. The dryer operates with 4-way divider which is connected to the heat source and the cooling fan. Grain dries in one dryer while the second is being cooled, emptied and re-filled.

Both dryers have their own elevators for recycling and discharging. For filling there's a third elevator. Machinery consists of two Special models.



TANDEM	2 x 2,5+3	2 x 3,5+3	2 x 4,5+4
Total volume [m³]	38,6	44,0	56,6
Heat cell volume [m³]	13,4	18,8	24,2
Storage container volume [m³]	21,6	21,6	28,8
Dryer height [m]	10,8	12,6	14,5
Elevator min. height [m] / fill elevator min. height [m]	11 / 13	12 / 14	14 / 16
Elevator [t / h] *	68	68	68
Fuse size [A] *	25	35	50

\* Recommendation / Other volumes also available!





## STANDARD EQUIPMENT


- ✓ 3x elevator
- ✓ Overpressure heater, vacuum heater or EcoHeater
- ✓ Control panel
- ✓ 2x pre-cleaner A200
- ✓ 2x bottom fan 1.5kW
- ✓ Tipping hopper 1x3m 1.5kW
- ✓ Service platform and ladder
- ✓ Circulate piping


## OPTIONS

- + Rain cover for tipping hopper
- + Seed Cleaner
- + Cyclone
- + GSM alarm
- + Control automation
- + Scale device
- + Additional switch for feeder
- + Rain covers for burner, elevator and pre-cleaner
- + Motored shutter for heat cell



## ARSKAMETALLI OY

 Saarentaantie 33  
FI-31400 Somero, Finland

 +358 2 748 9700

 [posti@arskametalli.fi](mailto:posti@arskametalli.fi)

© Arskametalli Oy 2021

All rights reserved. In the photos in this brochure or other publications may occur devices which are not standard equipment. Technical specifications are approximate.