





Mepu's versatile silo system allows quick construction of storage facilities in a new or existing building. The different silo elements can easily be assembled into a storage system that perfectly suits the customer's needs and premises.

Mepu square silos blend well with the environment. When installing a square silo, the space available can be utilized efficiently and the vertical poles carries the load of square silo building structure. After sealing by a suitable sealant, the elements are directly usable as external walls. The elements and posts can also be painted to the desired colour.

The Mepu silo system is CE marked, which means that the system complies with all the related EU requirements to durability and structure. The horizontally profiled elements made of galvanized steel are quick and simple to install. The silos are assembled using bolted joints.

FLAT BOTTOM AND CONE BOTTOM SILOS ARE AVAILABLE

The range includes both flat bottom and cone bottom silos. Cone bottom silos are available with 160-250mm unloading cones. Flat bottom and cone bottom silos can be equipped with manholes. Additionally, flat bottom silo can be equipped with auger lead-through and with straight and inclined unloading connection to silo wall element. We offer a wide range of accessories; for example, there are several shutter options.



			2000 [mm]		2500 [mm]		3000 [mm]	
2	T	H [m]	2	1	2	1	2	1
A	1	0,84	1,5	3	1,5	3	1,5	3
	2	1,68	1,5	3	1,5	3	1,5	3
	3	2,52	1,5	3	1,5	3	1,5	3
	4	3,36	1,5	3	1,5	3	2,5	3
	5	4,2	1,5	3	1,5	3	2,5	3
	6	5,04	1,5	3	2	3	2,5	3
	7	5,88	1,5	3	2	3	2,5	3
	8	6,72	1,5	3	2	3	2,5	5
	9	7,56	1,5	3	2	3	3	5
H	10	8,4	1,5	3	2	5	3	6
	11	9,24	1,5	3	2,5	5	3	6
	12	10,08	1,5	5	2,5	6		
	13	10,88	1,5	5	2,5	6		
	14	11,68	1,5	5	Layer Silo height			
	15	12,48	1,5	5				
	16	13,28	1,5	5				
	17	14,08	1,5	5				

1,5

1,5

18

19

14,88

2 Element thickness

1 Silo pole thickness

CONTACT US!

www.mepu.com



Mepu Oy reserves the right to make changes in the range, i.e. to the model, colour, equipment and price changes to the products it supplies, without any prior notification. The standard delivery contents of products may vary between different market areas. The photos in this brochure and in other publications may display equipment that are not included in the standard delivery. The performance values and technical specifications are intended as a guide. Check the delivery contents of the product with your Mepu reseller.



MEPU Oy

Mynämäentie 59 21900 Yläne F

Mynämäentie 59, 21900 Yläne, Finland tel. +358 2 275 4444, mepu@mepu.com

